

ASPERA

40W LED WATERPROOF LUMINAIRE (EMERGENCY KIT)

2914-K



Areas of Usage

- Emergency Exit Areas
- Car Parks
- Industrial Facilities
- Warehouses

General Features

Housing Material	: Polycarbonate
Diffuser Material	: Opal Polycarbonate
Product Color	: RAL 9010
Impact Resistance	: IK08
IP Rating	: IP65
Operating Temperature	: -20°C ~ +40°C
LED Lifespan	: 60.000 h - L70 @ Ta= 40°C
Product Lifespan	: 30.000 h
Dimmability	: Non-Dimmable
Mounting Type	: Surface Mounted

Emergency Kit Features

Power of Emergency Mode	: 3 W
Luminous of Emergency Mode	: 250 lm
Charging Time	: 24 h
Lighting Operating Time	: 2 h


Electrical Features

Power	: 40 W
Input Voltage	: 220-240V AC
Input Frequency	: 50/60 Hz
Power Factor	: $\geq 0,9$
Protection Class	: II


According to EU 2019/2015 Energy efficiency directive, there is a tolerance of $\pm 10\%$ for power and luminous flux values.

Optical Features

Luminous Flux	: 4200 lm
Luminous Efficacy	: 105 lm/W
Color Rendering Index CRI	: ≥ 80
Beam Angle	: 120°
Light Source	: Mid Power LED
Color Temperature	: 6500K
Photobiological Safety Group	: RG0





Light Distribution Curve (Polar)




Light Distribution Curve (Cone)

Dimensions & Weight




a	b	c	Weight
52mm	52mm	1200mm	520g


Suspension Set



Cable Length



Cable Gland



Packaging Data

Product Code	Units per Box (pcs)	Units per Carton (pcs)	Dimensions (width x length x height) (mm)	Weight (kg)
2914-K	1	20	296 x 1280 x 270	14,2

Color Temperature Options

Product Code	Color Temperature (Kelvin)	Luminous Flux (lm)
2914-K-01	6500	4200
2914-K-02	3000	4100
2914-K-03	4000	4200