

## ASPERA

### 40W LED WATERPROOF LUMINAIRE

2934

#### Areas of Usage

- Car Parks
- Industrial Facilities
- Warehouse



#### General Features

Housing Material	: Polycarbonate
Diffuser Material	: Opal Polycarbonate
Product Color	: RAL 9010
Impact Resistance	: IK08
IP Rating	: IP65
Operating Temperature	: -20°C ~ +40°C
LED Lifespan	: 60.000 h - L70 @ Ta= 40°C
Product Lifespan	: 30.000 h
Dimmability	: Non-Dimmable
Mounting Type	: Surface Mounted


#### Electrical Features

Power	: 40 W
Input Voltage	: 220-240V AC
Input Frequency	: 50/60 Hz
Power Factor	: $\geq 0,9$
Protection Class	: II


#### Optical Features

Luminous Flux	: 4200 lm
Luminous Efficacy	: 105 lm/W
Color Rendering Index CRI	: $\geq 80$
Beam Angle	: 120°
Light Source	: Mid Power LED
Color Temperature	: 6500K
Photobiological Safety Group	: RG0

According to EU 2019/2015 Energy efficiency directive, there is a tolerance of  $\pm 10\%$  for power and luminous flux values.




Light Distribution Curve (Polar)





Light Distribution Curve (Cone)

**Dimensions & Weight**



Suspension Set




Cable Length



a	b	c	Weight
52mm	52mm	1200mm	515g

Cable Gland



**Packaging Data**

Product Code	Units per Box (pcs)	Units per Carton (pcs)	Dimensions (width x length x height) (mm)	Weight (kg)
2934	1	20	296 x 1280 x 270	13,82

**Color Temperature Options**

Product Code	Color Temperature (Kelvin)	Luminous Flux (lm)
2934-01	6500	4200
2934-02	3000	4100
2934-03	4000	4200