

## 40W BACKLIGHT LED PANEL LUMINAIRE

4274

### Areas of Usage

- Office
- Hospitals
- Schools



### General Features

Housing Material	: Metal Sheet Housing
Diffuser Material	: PS Diffuser
Product Color	: RAL 9016
Impact Resistance	: 0,2 Nm
IP Rating	: IP20
Operating Temperature	: -20°C ~ +40°C
LED Lifespan	: 60.000 h - L70 @ Ta= 40°C
Product Lifespan	: 50.000 h
Dimmability	: Non-Dimmable
Mounting Type	: Recessed Mounted


### Electrical Features

Power	: 40 W
Input Voltage	: 220-240V AC
Input Frequency	: 50/60 Hz
Power Factor	: $\geq 0,9$
Protection Class	: II


### Optical Features

Luminous Flux	: 4400 lm
Luminous Efficacy	: 110 lm/W
Color Rendering Index CRI	: $\geq 80$
Beam Angle	: 120°
Light Source	: Mid Power LED
Color Temperature	: 6500K
Photobiological Safety Group	: RG0

*According to EU 2019/2015 Energy efficiency directive, there is a tolerance of  $\pm 10\%$  for power and luminous flux values.*






Light Distribution Curve (Polar)



Light Distribution Curve (Cone)

Dimensions & Weight



a	b	c	Weight
595mm	595mm	31mm	1365g

Packaging Data

Product Code	Units per Box (pcs)	Units per Carton (pcs)	Dimensions (width x length x height) (mm)	Weight (kg)
4274	1	10	625 x 660 x 360	15,55

Color Temperature Options

Product Code	Color Temperature (Kelvin)	Luminous Flux (lm)
4274-01	6500	3400
4274-02	3000	3250
4274-03	4000	3400