

## 3W SURFACE MOUNTED WALLWASHER LED LUMINAIRE

### 5301



#### Areas of Usage

- Gallery
- Offices
- Shopping Centers

#### General Features

Housing Material	: Aluminum
Diffuser Material	: Opal Polycarbonate
Product Color	: RAL 9006
Impact Resistance	: IK07
IP Rating	: IP65
Operating Temperature	: -20°C ~ +40°C
LED Lifespan	: 50.000 saat - L70 @ Ta= 40°C
Product Lifespan	: 30.000 h
Dimmability	: Non-Dimmable
Mounting Type	: Surface Mounted Installation


#### Electrical Features

Power	: 3 W
Input Voltage	: 220-240V AC
Input Frequency	: 50/60 Hz
Power Factor	: $\geq 0,9$
Protection Class	: I

#### Optical Features


Luminous Flux	: 480 lm
Luminous Efficacy	: 160 lm/W
Color Rendering Index CRI	: $\geq 80$
Beam Angle	: 30°
Light Source	: Mid Power LED
Color Temperature	: 6500K
Photobiological Safety Group	: RG1

*According to EU 2019/2015 Energy efficiency directive, there is a tolerance of  $\pm 10\%$  for power and luminous flux values*




Light Distribution Curve (Polar)

**Dimension & Weight**



a	b	c	Weight
49mm	55mm	100mm	320g

Cable Length



**Packaging Data**

Product Code	Units per Box (pcs)	Units per Carton (pcs)	Dimesions (width x length x height) (mm)	Weight (kg)
5301	1	1	800 x 110 x 75	0.55

**Color Temperature Options**

Product Code	Color Temperature (Kelvin)	Luminous Flux (lm)
5301-01	6500	480
5301-02	3000	420
5301-03	Red	-
5301-04	Green	-
5301-05	Blue	-
5301-06	Amber	-
5301-08	Naturel White	480