

24W RECESSED WALLWASHER LED LUMINAIRE

5316

Areas of Usage

- Gallery
- Offices
- Shopping Centers



General Features

Housing Material	: Aluminum
Diffuser Material	: Opal Polycarbonate
Product Color	: RAL 9006
Impact Resistance	: IK07
IP Rating	: IP65
Operating Temperature	: -20°C ~ +40°C
LED Lifespan	: 50.000 saat - L70 @ Ta= 40°C
Product Lifespan	: 30.000 h
Dimmability	: Non-Dimmable
Mounting Type	: Recessed Installation


Electrical Features

Power	: 24 W
Input Voltage	: 220-240V AC
Input Frequency	: 50/60 Hz
Power Factor	: ≥0,9
Protection Class	: I

Optical Features


Luminous Flux	: 3840 lm
Luminous Efficacy	: 160 lm/W
Color Rendering Index CRI	: ≥80
Beam Angle	: 30°
Light Source	: Mid Power LED
Color Temperature	: 6500K
Photobiological Safety Group	: RG1

According to EU 2019/2015 Energy efficiency directive, there is a tolerance of ±10% for power and luminous flux values




Light Distribution Curve (Polar)

Dimension & Weight



Cable Length



Packaging Data

Product Code	Units per Box (pcs)	Units per Carton (pcs)	Dimesions (width x length x height) (mm)	Weight (kg)
5316	1	1	80 x 725 x 75	2.35

Color Temperature Options

Product Code	Color Temperature (Kelvin)	Luminous Flux (lm)
5316-01	6500	3840
5316-02	3000	3360
5316-03	Red	-
5316-04	Green	-
5316-05	Blue	-
5316-06	Amber	-
5316-08	Naturel White	3840