

## 75W SURFACE MOUNTED SQUARE LINEAR LED LUMINAIRE

### 5391



#### Areas of Usage

- Gallery
- Offices
- Shopping Centers

#### General Features

Housing Material	: Aluminum
Diffuser Material	: Opal Polycarbonate
Product Color	: RAL 9005, RAL 9006, RAL 9016
Impact Resistance	: IK0,2Nm
IP Rating	: IP20
Operating Temperature	: -20°C ~ +40°C
LED Lifespan	: 50.000 saat - L70 @ Ta= 40°C
Product Lifespan	: 50.000 h
Dimmability	: Non-Dimmable
Mounting Type	: Surface Installation


#### Electrical Features

Power	: 75 W
Input Voltage	: 220-240V AC
Input Frequency	: 50/60 Hz
Power Factor	: $\geq 0,9$
Protection Class	: II

#### Optical Features


Luminous Flux	: 12000 lm
Luminous Efficacy	: 160 lm/W
Color Rendering Index CRI	: $\geq 80$
Beam Angle	: 120°
Light Source	: Mid Power LED
Color Temperature	: 6500K
Photobiological Safety Group	: RG1

*According to EU 2019/2015 Energy efficiency directive, there is a tolerance of  $\pm 10\%$  for power and luminous flux values*



Light Distribution Curve (Polar)

**Dimension & Weight**



a	b	c	Weight
50mm	80mm	600mm	2240g

Cable Length



600mm

**Packaging Data**

Product Code	Units per Box (pcs)	Units per Carton (pcs)	Dimesions (width x length x height) (mm)	Weight (kg)
5391	1	1	600x600x80	2.37

**Color Temperature Options**

Product Code	Power (W)	Luminous Flux (lm)	Diameter (cm)
5392	100	15680	80x80
5393	130	20000	100x100
5394	155	24300	120x120